

S-Series

S-18/S-19

STYLISH DESIGN

AG Neovo S-Series Displays

Made for those who
want a stylish award winning display

Elegant & Rugged Design

Smart exterior with
exceptional strength

Brilliant Display

Patent pending NeoV
Crystal Optic Filter offers
superb color definition
and image sharpness

Ease Of Use


A host of input options,
including analog, s-video
and DVI-Digital

Desk/Arm/Wall Flexibility

VESA Compatible LCD
display arm or wall
mount kit both available

Customer Satisfaction

Global after-sales
service, and a 3 year
limited warranty



Features

Neo-V Crystal Optic Filter
18"/19" TFT Active Matrix Screen
1280x1024 Resolution
Foldable Small Footprint Stand
Analog, Video & Digital Inputs

AG neovo

A Different Class Of Display

S-Series Displays



NeoV Crystal Optic Filter

Triple coated on both sides, the NeoV Crystal Optic Filter offers anti-glare, anti-reflective properties, while delivering greater color definition.



Wide Viewing Angle

Wide angle viewing technology offers greater viewing clarity even when the display is seen from different angles.



Video In Port

Connect DVD, VCR or other video devices directly via a video in port.



DVI-D Port

Take advantage of the latest in technology, by connecting to the DVI-D port for a clearer image.



Auto-Adjustment

Automatically adjusts screen settings for an optimal image, without changing settings manually.



LCD Panel Protection

Protects the LCD panel from potential damage caused by repeated touching of the surface.



OSD

On-Screen Display (OSD) makes adjusting the display settings quick and convenient.



Total Flat Display

A completely flat display, with absolutely no curvature, generates a truer and less distorted view.



LCD Display Arm

Advanced gas-spring suspension guarantees smooth stable operation, and flexibility of use.



Wall Mount Kit

Mount the LCD display on the wall to save even more valuable desktop space.



Security Lock

Increase security by anchoring the LCD display to an immovable object. Compatible with Kensington® security locks.



Specifications

	S-18	S-19
Panel	Panel Type: TFT LCD Panel Size: 18.1" (459.7mm) Max. Resolution: SXGA 1280 x 1024 Pixel Pitch: 0.2805mm Brightness: 250cd/m ² (Typical) Contrast Ratio: 550:1 (Typical) Surface Treatments: Hard Coating (3H) & Anti-glare treatment Viewing Angle (H/V): 170°/170° (Minimum) Display Color: 16.7M Response Time: 16ms /9ms (Typical) Wide Viewing Angle: Yes Frequency: Horizontal: 30kHz - 80kHz Vertical: 50Hz - 75Hz Max. Pixel Clock: 135MHz	Panel Type: TFT LCD Panel Size: 19.0" (480mm) Max. Resolution: SXGA 1280 x 1024 Pixel Pitch: 0.294mm Brightness: 250cd/m ² (Typical) Contrast Ratio: 500:1 (Typical) Surface Treatments: Hard Coating (2H) & Anti-glare treatment Viewing Angle (H/V): 170°/170° (Minimum) Display Color: 16.7M Response Time: 15ms /10ms (Typical) Wide Viewing Angle: Yes Frequency: Horizontal: 30kHz - 80kHz Vertical: 50Hz - 75Hz Max. Pixel Clock: 135MHz
Inputs	Analog Video: 15-Pin Mini D-Sub Digital: 4-Pin Mini Din S-Video CVBS Jack 29-Pin DVI-D	Analog Video: 15-Pin Mini D-Sub Digital: 4-Pin Mini Din S-Video CVBS Jack 29-Pin DVI-D
Connector	Power: 3-Pin AC Plug	Power: 3-Pin AC Plug
NeoV Crystal Optic Filter	Thickness: 2.8mm (0.11") Reflection Rate: < 1% Transmission Rate: > 94% Hardness (Moh's Rating): > 6H	Thickness: 2.8mm (0.11") Reflection Rate: < 1% Transmission Rate: > 94% Hardness (Moh's Rating): > 6H
Tilt/Swivel	Tilt Angle / Swivel: 5° ~ 25° (Tilt)	Tilt Angle / Swivel: 5° ~ 25° (Tilt)
Mounting	VESA FPMPMI	Yes (100mm)
Dimensions	Net (W x H x D): 436x 426x 200mm (17.2" x 16.8" x 7.9") Packing (W x H x D): 550 x 576 x 220mm (21.7" x 22.7" x 8.7")	Net (W x H x D): 436 x 426 x 200mm (17.2" x 16.8" x 7.9") Packing (W x H x D): 550 x 576 x 220mm (21.7" x 22.7" x 8.7")
Weight	Net Weight: 8.0Kg (17.6lb) Gross Weight: 11.1Kg(24.4lb)	Net Weight: 8.2Kg (18.0lb) Gross Weight: 11.3Kg(24.9lb)
Regulation Approval	Safety & EMI: FCC, UL/CUL, EPA, TUV/GS, CE, NORDIC, TCO95, NUTEK, BSMI, VCCI, CCC, CB, ISO13406 VESA: DDC1/2B, DPMS	Safety & EMI: FCC, UL/CUL, EPA, TUV/GS, CE, NORDIC, TCO95, NUTEK, BSMI, VCCI, CCC, CB, ISO13406 VESA: DDC1/2B, DPMS
Power	Power AC Consumption: 100~240V, 50~60Hz < 48W (On), < 5W (Stand-by) < 5W (Off)	Power AC Consumption: 100~240V, 50~60Hz < 48W (On), < 5W (Stand-by) < 5W (Off)

All specifications are subject to change without prior notice. © 2003 Associated Industries China Inc. The name AG Neovo is a trademark of AIC. All other trademarks are the property of their respective owners.

Optional Accessories



A Different Class Of Display

